

Amendments to the Claims

Please amend the claims as follows:

1. (Original) A shutter for a building aperture comprising:

a shutter curtain having a first and a second face, the shutter curtain being locatable in the aperture;

a filament spanning the aperture and lying in a plane substantially parallel and adjacent to the first face of the shutter curtain; and

a tensioning device for applying tension to the filament to provide support to the curtain against flexure thereof in a direction towards the filament.
2. (Original) The shutter according to claim 1, wherein the filament comprises a metallic wire.
3. (Original) The shutter according to claim 1, wherein the tensioning device comprises a winch around which the filament is wound.
4. (Original) The shutter according to claim 3, wherein the winch comprises a locking element for selectively locking the winch against unwinding.
5. (Original) The shutter according to claim 1, wherein the shutter further comprises first and second guides which respectively receive and guide opposing lateral edges of the curtain, the guides being located on opposing lateral edges of the aperture.
6. (Original) The shutter according to claim 5, wherein a first end of the filament is retained on the first guide and the tensioning device is provided on the second guide, a second end of the filament being received by the tensioning device.

7-9. (Cancelled)

10. (Original) The shutter according to claim 1, wherein the shutter further comprises a second filament spanning the aperture.

11. (Original) The shutter according to claim 10, further comprising a second tensioning device for applying tension to the second filament.

12. (Original) The shutter according to claim 10, wherein the second filament lies in a plane substantially parallel and adjacent to the second face of the shutter curtain.

13. (Cancelled)

14. (Original) The shutter according to claim 1, wherein a storage device is provided for storing at least part of the filament when not under tension.

15. (Original) The shutter according to claim 14, wherein the storage device comprises an elastic element biasing the filament in a direction into the storage device.

16. (Currently Amended) A storm retainer for retaining a shutter curtain against flexure, the shutter curtain being located across an aperture of a building and having a first face and a second face, the storm retainer comprising:

a filament extending across the first face;

an anchor attached to a first portion of the filament and securing the first portion with respect to the aperture;

a tensioning device, the tensioning device being secured with respect to the aperture and being attached to a second portion of the filament, actuation of the tensioning device causing tensioning of the filament from the first portion to the second portion.

17. (Original) The storm retainer according to claim 16, wherein the anchor attaches to the building adjacent to the aperture.

18. (Original) The storm retainer according to claim 16, wherein the shutter curtain is provided with a frame and the anchor attaches to the frame.

19-22. (Cancelled)

23. (Original) A method of restraining against flexure of a shutter provided in a building aperture, the method comprising:

providing a substantially inextensible filament;

disposing the filament across the aperture to lie substantially in the plane of the shutter; and

applying tension to the filament.

24. (Original) A shutter for a building aperture comprising:

a shutter curtain having a first and a second face, the shutter curtain being locatable in the aperture;

a flexible strengthening means spanning the aperture and lying in a plane substantially parallel and adjacent to the first face of the shutter curtain; and

tensioning means for applying tension to the flexible strengthening means to provide support to the curtain against flexure thereof in a direction towards the flexible strengthening means.

25. (Original) The shutter according to claim 24, wherein the shutter further comprises first and second guides which respectively receive and guide opposing lateral edges of the curtain, said guides being located on opposing lateral edges of the aperture.

26. (Original) The shutter according to claim 25, wherein the flexible strengthening means includes a first end and a second end, and wherein the first end of the flexible strengthening means is retained on said first guide and said tensioning means is provided on the second guide, said second end of the flexible strengthening means being connected by attachment means to the tensioning means.

27. (Currently Amended) The shutter according to claim 26, wherein said tensioning means ~~comprise~~ comprises a knob having a threaded extension which receives the second end of said flexible strengthening means.

28. (Original) The shutter according to claim 27 wherein the tensioning means further comprises a movable restraining element which engages said second guide.

29. (Original) The shutter according to claim 27 wherein said tensioning means further comprises means for engaging the threaded extension.

30. (Currently Amended) The shutter according to claim 28 wherein the means for engaging the threaded extension ~~comprise~~ comprises a nut for securing the threaded extension of the tensioning means.

31. (Original) The shutter according to claim 29 wherein the tensioning means is disposed within a slot within the guide such that the nut may be engaged by the second guide, and whereby the flexible strengthening means may be maintained at a desired tension.

32. (Currently Amended) The shutter according to claim 27 wherein the means for engaging the threaded extension ~~comprise~~ comprises a threaded receptacle affixed to the second guide.

33. (Currently Amended) The shutter according to claim 26, wherein the attachment means ~~comprise~~ comprises spherical terminus of the flexible strengthening means, whereby the diameter of the spherical terminus is large enough to allow engagement with the tensioning means.

34. (Original) The shutter according to claim 24, wherein a second flexible strengthening means spans the aperture and lies in a plane substantially parallel and adjacent to the second face of the shutter curtain.

35. (Cancelled)

36. (Original) The shutter according to claim 1 wherein said tensioning device comprises the shutter curtain whereby the shutter curtain provides tension to the filament as the shutter curtain is flexed or bowed by the wind.

37. (Original) The shutter according to claim 24 wherein said tensioning device comprises the shutter curtain whereby the shutter curtain provides tension to the flexible strengthening device as the shutter curtain is flexed or bowed by the wind.

38. Cancelled.

39. (New) The storm retainer of claim 16, further comprising:
a second filament extending across the second face;

a second anchor attached to a first portion of the second filament and securing the first portion of the second filament with respect to the aperture; and

a second tensioning device, the second tensioning device being secured with respect to the aperture and being attached to a second portion of the second filament, actuation of the second tensioning device causing tensioning of the second filament from the first portion to the second portion of the second filament.

40. (New) The method of claim 23 wherein

the shutter has a first face and a second face;

the filament is provided across the first face; and

further comprising:

providing a second substantially inextensible filament;

disposing the second filament across the second face to lie substantially in the plane of the shutter; and

applying tension to the second filament.